

PY LI UPS 3kVA / 2.7kW R/T (2U)

Výrobce:

FUJITSU / APC

Specifikace:

3000VA / 2700W Tower/Rack convertible (Rack 2U) Line Interactive (VI) UPS (SMX3000RMHV2U) Black, **8x IEC320 C13** (10A) output connections 1x IEC320 C19 (16A) output connections Outlets are arranged in three controllable groups 1x IEC320 C20 (16A) + Power Cord with IEC309 (CEE) blue plug. **incl. Network Management Card AP9630** incl. Rackmount kit incl. standing feets for Tower incl. control cable for the first server USB and COM-port (black) LCD front

P / n výrobce: S26361-K1426-V300

Karta managmentu : UPS Network Management adapter for 10/100 Base-T and Telnet connectors, supports 10/100 Mbit/s autosence and the protocols Telnet, FTP, TFTP, WEB and SNMP

OS list for LAN connectivity by help of APC PowerChute Network Shutdown (PCNS) v3.0.1 on CD in the Box

Uses the installed Web Management card in the UPS

Windows Server Operating Systems

- Windows Server 2012 with Hyper-V support
- Windows Server 2008 R2 with Hyper-V support

Linux Enterprise OS

- Red Hat Enterprise Linux 5 32-bit and 64-bit
- Red Hat Enterprise Linux 5 [KVM / XEN] 64-bit
- Red Hat Enterprise Linux 6 32-bit and 64-bit
- Red Hat Enterprise Linux 6 [KVM] 64-bit
- SUSE Linux Enterprise Server 10 32-bit and 64-bit
- SUSE Linux Enterprise Server 11 32-bit and 64-bit
- SUSE Linux Enterprise Server 11 [XEN] 64-bit

VMware Hypervisor

- ESX 4.0 (inc. FT)



- ESX 4.1 (inc. FT)
- ESXi 4.1 Installable (inc. FT)
- ESXi 5.0 (inc. FT)
- ESXi 5.1 (inc. FT)
- ESXi 5.5 (inc. FT)
- ESXi 6 (inc. FT)